

CM034942

COUNTERS • MULTI-FUNCTION COUNTERS



MECHANICAL DATA

Ambient temperature (MAX)	50 °C
Degree of protection (IP)	IP65
Height	48 mm
Housing material	Polycarbonate
Installation depth	108 mm
Length	106.6 mm
Mounting method	Front mounting
Width	48 mm

ELECTRICAL DATA

Counting frequency	10 kHz
Display	LED
Input voltage frequency	50 Hz
Number of decades	5
Number of pins	15
Number of presets to be set	2
Number of switching outputs	2
Operating voltage (MAX)	265 V
Operating voltage (MIN)	85 V
Power consumption	4 W
Primary voltage	265 V
Pulse counter	Yes
Rated control supply voltage U_s at AC 50HZ (MAX)	265 V
Rated control supply voltage U_s at AC 50HZ (MIN)	85 V
Switching capacity	30 VA
Switching current	1 A
Switching voltage	250 V
Timed output	99.99 s
Transducer power supply current	60 mA
Type of 2nd switching output	Relay contact
Type of electrical connection	Screw connection

ELECTRICAL DATA

Type of switching function	Change-over contact (NO/NC)
Type of switching output	Relay contact
Voltage type	AC
With elapsed-time counting function	Yes
With reset function	Yes

OTHER DATA

Number of characters	5
----------------------	---

DIMENSIONAL DRAWING**INSTALLATION**

Mounting / Installation may only be carried out by a qualified electrician!

DISPOSAL**SAFETY WARNINGS**

Before initial operation, please make sure to follow all safety instructions that may be provided in the product information!

Never use these devices in applications where the safety of a person depends on their functionality.