

OK639196

OPTICAL SENSORS • CONTRAST SCANNERS

Contrast scanners are capable to distinguish the the visual differences (e.g. reflectivity, brightness differences) between adjacent areas. In general, the devices project a light spot on an object's surface and analyze the reflected light. Fiber optic amplifier versions can be used in addition to the incident light mode also in the transmitted light mode. Contrast scanners are versatile. They can be used, among other things, for position control of printing or color marks, distinction of brightness variations or in the intensity control of luminous objects (like LEDs, displays etc.).

MECHANICAL DATA

Ambient temperature	-20 °C ... 55 °C
Degree of protection (IP)	IP64
Housing design	Cuboid
Housing material	Aluminium
Sensor height	91 mm
Sensor length	65 mm
Sensor width	65 mm
Storage temperature	85 °C
Storage temperature	-20 °C
With fiber optics connection	No
With interchangeable lens	Yes

ELECTRICAL DATA

Analogue output 0 mA ... 20 mA	No
Analogue output 0 V ... 10 V	Yes
Analogue output -10 V ... +10 V	No
Analogue output 4 mA ... 20 mA	Yes
High scanning frequency	Yes
Max. output current	100 mA
Operating voltage	24 V ... 24 V
Programmable via software	Yes
Rated control supply voltage U_s at DC	24 V ... 24 V
Reverse polarity protection	Yes
Sensing range	60 mm ... 240 mm
Setting procedure	Parameterization
Short-circuit-proof	Yes
Switching frequency	60000 Hz
Type of electrical connection	Connector M9
Type of switching function	Programmable/configurable
Type of switching output	PNP/NPN
Voltage type	DC

ELECTRICAL DATA

With blanking function	No
With communication interface, RS-232	Yes
With LED display	Yes
With time function	No

OPTICAL DATA

Light source	White light
--------------	-------------

OTHER DATA

For counting tasks	Yes
--------------------	-----

DIMENSIONAL DRAWING**INSTALLATION**

Mounting / Installation may only be carried out by a qualified electrician!

DISPOSAL**SAFETY WARNINGS**

Before initial operation, please make sure to follow all safety instructions that may be provided in the product information!