

## AV991353

### CONNECTION TECHNOLOGY • CABLE SOCKETS /CONNECTORS TWO-SIDED PRE-ASSEMBLED

ipf cable sockets are used primarily for establishing the electrical connection of sensors. Their features are characterized by rugged design, the highest protection classes (IP67 | IP68 | IP69K) and, if desired, with 360° shielding. With the features: bus-ready, suitable for use with drag chains and robots, resistance to oil and chemicals, resistance to welding sparks, their resistance to cleaning agents or high-pressure and steam-jet cleaning, the expanded temperature range of up to +230°C, the rapid interconnection technology and special data transmission properties, the cable sockets meet all requirements in automation technology.

#### MECHANICAL DATA

Cable length	1 m
Material of cable sheath	PUR (Polyurethane)
Number of wires	7
Positioning of cable feed, field side	Angled
Positioning of cable feed, housing side	Straight
Suitable for trailing chain	Yes

#### ELECTRICAL DATA

Number of electrical connections, field side	2
Number of electrical connections, housing side	1
Number of pins	7
Number of pins, housing side	7
Type of cable	Multi-core
Type of electrical connection, field side	Binder
Type of electrical connection, housing side	Binder 680
Type of plug-in contact, field side	Female (socket)
Type of plug-in contact, housing side	Male (plug)

#### DIMENSIONAL DRAWING

#### INSTALLATION



Mounting / Installation may only be carried out by a qualified electrician!

#### DISPOSAL



#### SAFETY WARNINGS

Before initial operation, please make sure to follow all safety instructions that may be provided in the product

information!