

## LT060291

### FIBER OPTIC SENSORS • FIBER OPTICS COLOR RECOGNITION

Fiber optics in combination with the appropriate fiber optic amplifier function as contactless and wear-free position switches that can also be used in harsh environmental conditions. They detect objects independent of their characteristics (e.g., shape, color, surface structure, material). Because the ends and heads of the fiber optics have small dimensions and the fiber optics are flexible, very elegant solutions can be created for detecting objects in places that are difficult to access. Fiber optics can be used without special precautions in potentially explosive areas and in zones with electrical and/or magnetic fields (high-voltage installations, electrical welding equipment) as their function is not thereby affected. Fiber optics are available in versions for implementing the function as through-beam sensor or diffuse reflection sensor.



#### MECHANICAL DATA

Fiber diameter	2.5 mm
Fiber optics core material	Glass
Heavy soiling	Yes
Housing design	Cylinder plain
Material of cable sheath	Silicone
Number of fibers	1
Overall length	600 mm
Punching tools	Yes
Sheathing material	Metal inner helix/braided glass fibers
Strong vibration / motion	Yes
Version	Diffuse reflection sensor-color sensors

#### ELECTRICAL DATA

Analogue output 4 mA ... 20 mA	No
Light exit	Axial

#### DIMENSIONAL DRAWING

##### INSTALLATION



Mounting / Installation may only be carried out by a qualified electrician!

##### DISPOSAL



#### SAFETY WARNINGS

Before initial operation, please make sure to follow all safety instructions that may be provided in the product information!

Never use these devices in applications where the safety of a person depends on their functionality.