

CM030943**COUNTERS • MULTI-FUNCTION COUNTERS****MECHANICAL DATA**

Ambient temperature (MAX)	50 °C
Degree of protection (IP)	IP65
Height	48 mm
Housing material	Polycarbonate
Length	106.6 mm
Suitable for serial installation	No
Width	48 mm

ELECTRICAL DATA

2. output voltage at AC	250 V ... 250 V
2. output voltage at DC	110 V ... 110 V
Counting frequency	10 kHz
Display	LED
Max. output current 1	1 A
Max. output current 2	1 A
Number of decades	5
Number of pins	15
Number of presets to be set	2
Number of switching outputs	2
Power consumption	4 W
Pulse counter	Yes
Rated control supply voltage U_s at DC	12 V ... 30 V
Switching current	1 A
Switching voltage	250 V
Timed output	99.99 s
Transducer power supply current	60 mA
Type of 2nd switching function	Normally open contact (NO)
Type of 2nd switching output	Relay contact
Type of electrical connection	Screw connection
Type of switching function	Normally open contact (NO)
Type of switching output	Relay contact

ELECTRICAL DATA

Voltage type	DC
With reset function	No

DIMENSIONAL DRAWING**INSTALLATION**

Mounting / Installation may only be carried out by a qualified electrician!

DISPOSAL**SAFETY WARNINGS**

Before initial operation, please make sure to follow all safety instructions that may be provided in the product information!