

NB800-LSu-GE

Vehicle Router with LTE + ETH + USB + GNSS + E-Mark

Compact general purpose onboard communication unit for special vehicles.



Keyfeatures

Mobile / Cellular	1x LTE, UMTS, GSM
SIM	1x Micro SIM / 1x eSIM chip (on request)
Ethernet	1x Fast Ethernet
USB	USB 2.0 Host
Positioning	Multi-GNSS
Operation Temperature	-40 °C to +70 °C
Software	Routing, Network Services, VPN, Firewall, Link Management, Supervisor, SDK, free updates
Compliance	CE (RED), Vehicle (UNECE-R10, UNECE-R118)
Modularity	Extensions on request

Product description

The compact NB800 is the cost-effective solution for a robust on-board Internet connection in vehicles.

Applications

- Emergency Services
- Smart Traffic
- CCTV
- Tracking
- Voice Communication
- Ticketing
- CCTV
- Fleet Management

Specifications

Mobile / Cellular	Standard	1x Multimode LTE, UMTS, GSM for EMEA 4G - LTE B1 (2100), B3 (1800), B5 (850), B7 (2600), B8 (900), B20 (800) 3G - DC-HSPA+/UMTS B1 (2100), B2 (1900), B5 (850), B8 (900) 2G - GSM/GPRS/EDGE B2 (1900), B3 (1800), B5 (850), B8 (900) Category LTE Cat 4 Antenna ports 2x2 MIMO Data rate down / up (max) 150 Mbps / 50 Mbps Voice CSFB (with optional Software License) FCC ID XPTYOBYL210
	Region	Europe, Middle East and Africa (EMEA)
	Connectors	2x SMA female
	SIM	1x Micro SIM - 3FF / eSIM Chip (on request)

Ethernet	Standard	1x Fast Ethernet Ethernet standard 100BASE-TX, Auto MDIX Speed 10/100 Mbps
	Connector	1x RJ45

Positioning	Standard	1x Multi-GNSS Receiver BeiDou, Galileo, GLONASS, GPS/QZSS 72-channel u-blox M8 engine 3 concurrent GNSS channels Antennas Active or passive Accuracy Up to 2.5 m CEP Sensitivity Up to -167 dBm Services Standalone, Assisted GPS Data server with JSON, NMEA data stream
	Connector	1x SMA female

USB	Standard Connector	1x USB 2.0 Host 1x Type A
System	Core Module Slots	1 GHz single core, 512 MB RAM, 4 GB flash, HW Rev. B02 1x Shield
Software	Features	<p>NetModule Router Software (supported features depending on product variant)</p> <p>Package The standard software package includes an intuitive user interface, covering all modern routing protocols and enables efficient mass deployment.</p> <p>General Fail-safe update (FOTA), upgrade via USB, HTTP(S), (S)FTP or TFTP, remote CLI & WebGUI, RADIUS authentication, Simple Certificate Enrollment Protocol (SCEP), Hardware- und Software Watchdog</p> <p>Remote Management Manage and monitor devices with SNMP V1/V2/V3, Netmodule vendor MIB, telnet, SSH, or HTTP/HTTPS</p> <p>Cellular Networking Multi-SIM / eSIM support (optional license), multi-APN support, signal strength monitoring, dedicated bearers, CSFB/VoLTE calls (optional license)</p> <p>Wireless LAN Access Point, Client Mode, Mesh Point or Dual Modes (Mesh Access Point / Access Point - Client), WLAN Pseudo-Bridge Client Mode: Multiple Client SSID Profile, Encryption: Open, WEP, WPA1/2/3-Personal, WPA1/2/3-Enterprise. Fast Roaming: Fast BSS Transition (802.11r), PreAuthentication, Protected Management Frames (802.11w) AP Mode: Multi-SSIDs (up to 8) Encryption: Open WPA1/2/3-Personal, WPA1/2/3-Enterprise Fast Roaming: Fast BSS Transition (802.11r), PreAuthentication, DFS support Protected Management Frames (802.11w) Client Tracking, Band Steering, Hide SSID broadcasting, Isolate Clients, Accounting, Short guard Intervall Mesh Mode (802.11s): Encryption: None, SAE. Gateway announcements</p> <p>Link Management Link prioritization, link aggregation, load balancing, multipath-TCP, IP-passthrough, link supervision,</p> <p>Services DHCP Client/Server, DNS Caching Server, Email, SMS Service, NTP Client/Server, SNTP Server, DynDNS, SSH Server, SNMP Agent, HTTP/HTTPS/FTP Server, IPv6 for WAN, 802.1x over Ethernet, MQTT Broker Voice Gateway (SIP, Call Routing, Audio with optional license) Coovachilli Hotspot</p> <p>Routing Destination, policy, multipath, mobile-IP, OSPF, BGP, multicast, TCP-MSS clamping, bridging discovery protocols LLDP, CDP, SONMP, EDP, FDP, IRDP, VRRP, STP/RSTP, VRRP, VLAN, PPPoE, VXLAN</p> <p>VPN OpenVPN, IPsec (IKEv1 and IKEv2), PPTP, GRE, L2TP, CSD dial-in, Certificate revocation service</p> <p>Firewall Stateful firewall, connection tracking, NAT, NAT, masquerading, bridge filtering, Adress translation (based on SRC and DST ports)</p> <p>Encryption supporting password protected PKCS12 files, integrated random certificate key generator, "Let's encrypt" certificate, ECC (Certificates with Elliptic Cryptography)</p> <p>Quality of Service Diffserv, SFQ, HTB, Priority-based Queuing, Netflow (Softflow)</p> <p>Programmability SDK</p> <p>Troubleshooting Logging, Ping, Traceroute, Tcpdump, Speed-test</p>
	Licenses	<p>GNSS</p> <p>Enabled service GNSS location service Server with JSON-, NMEA stream</p>
Power	Input Voltage	12, 24 VDC Nominal voltages 12, 24 VDC Absolute voltages 12 VDC to 24 VDC (-20 % / +20 %)
	Connector Consumption	1x Terminal block header 3.5 mm 5 W (average), 10 W (max)
Mounting		Bracket
Dimensions	W x H x D	Width 85/111 mm x height 32 mm x depth 110 mm
Weight		220 g
Environment	Operating Temperature Ingress Protection Level	-40°C to +70°C IP40
MTBF		340'000 h / 38.8 years, according SN29500 at environmental temperature 40 °C
Certifications	Compliance Domain	CE according to 2014/53/EU (RED), 2011/65/EU (RoHS), Vehicle according to UNECE-R10, UNECE-R118 Vehicle
Order Code		NB800-LSu-GE