

VK003S79

CONNECTION TECHNOLOGY • CABLE SOCKETS FIELD-ATTACHABLE

ipf cable sockets are used primarily for establishing the electrical connection of sensors. Their features are characterized by rugged design, the highest protection classes (IP67 | IP68 | IP69K) and, if desired, with 360° shielding. With the features: bus-ready, suitable for use with drag chains and robots, resistance to oil and chemicals, resistance to welding sparks, their resistance to cleaning agents or high-pressure and steam-jet cleaning, the expanded temperature range of up to +230°C, the rapid interconnection technology and special data transmission properties, the cable sockets meet all requirements in automation technology.



MECHANICAL DATA

| | |
|---|----------|
| Degree of protection (IP) | IP67 |
| Number of wires | 4 |
| Perm. ambient temperature of cable, fixed cable (MAX) | 85 °C |
| Perm. ambient temperature of cable, fixed cable (MIN) | -25 °C |
| Positioning of cable feed, housing side | Straight |


ELECTRICAL DATA

| | |
|---|-------------|
| Line diameter | 5.1 mm |
| Number of pins | 4 |
| Rated current I _n | 4 A |
| Rated voltage | 32 V |
| Shielded | No |
| Suitable for self-assembly | Yes |
| Type of electrical connection, housing side | M8 |
| Type of plug-in contact, housing side | Male (plug) |
| With LED display | No |

OTHER DATA

| | |
|-----------------|----|
| Flame resistant | No |
| Halogen-free | No |
| IR-networked | No |

CONNECTION



Colors: 1 = BN (brown), 2 = WH (white), 3 = BU (blue), 4 = BK (black)

Functions:

DIMENSIONAL DRAWING

INSTALLATION



Mounting / Installation may only be carried out by a qualified electrician!

DISPOSAL



SAFETY WARNINGS

Before initial operation, please make sure to follow all safety instructions that may be provided in the product information!

Never use these devices in applications where the safety of a person depends on their functionality.