

**KN991040**

**CAPACITIVE SENSORS • NORM SWITCHING DISTANCE**

Capacitive proximity switches are contact-free sensors. They detect metallic and non-metallic objects, regardless of whether they move or not. The achievable sensing range of the devices depends on the object material, its dimensions and the response sensitivity, which is set via a potentiometer. The vibration-resistant sensors can be approached laterally or frontally. Capacitive proximity switches are used for presence detection (e.g. sealing detection), positioning (e.g. PET bottles), counting (e.g. plastic caps), level detection (e.g. lubricant) or distance measurements (e.g. thickness measurement) of solid and liquid materials.



**MECHANICAL DATA**

Mechanical mounting condition for sensor	Non-flush
Pressure-proof	No

**ELECTRICAL DATA**

Cascadable	No
Max. output current	250 mA
Suitable for safety functions	No
Supply voltage	10 V ... 35 V
Switching distance	30 mm
Type of electrical connection	Connector M12
Type of switching output	PNP
Voltage type	DC
With monitoring function of downstream devices	No

**DIMENSIONAL DRAWING**

**INSTALLATION**



Mounting / Installation may only be carried out by a qualified electrician!

**DISPOSAL**



**SAFETY WARNINGS**

Before initial operation, please make sure to follow all safety instructions that may be provided in the product information!