

OR700300

OPTICAL SENSORS • RETRO-REFLECTIVE SENSORS

Optical sensors function contactlessly. They detect objects independent of their characteristics (e.g., shape, color, surface structure, material). The basic operating principle is based on the transmission and reception of light. There are three different versions: 1. The through-beam sensor consists of two separate devices, a transmitter and a receiver that are aligned with one another. If the light beam between the two devices is interrupted, the switching output integrated in the receiver changes its status. 2. With the retro-reflective sensor, the transmitter and receiver are located in one device. The emitted light beam is reflected back to the receiver by a reflector that is to be mounted opposite the device. As soon as the light beam is interrupted, the switching output integrated in the device changes its status. 3. With the diffuse reflection sensor, the transmitter and receiver are in one device. The emitted light beam is reflected by the object that is to be detected. As soon as the receiver detects the reflected light, the switching output integrated in the device changes its status.



MECHANICAL DATA

Degree of protection (IP)	IP67
Housing design	Cuboid
Housing material	Zinc die-cast
Material of optical surface	Glass
Reflector included in the scope of delivery	No
Sensor height	90 mm
Sensor length	70 mm
Sensor width	30 mm

ELECTRICAL DATA

Alarm output	Yes
Decay time	25 ms
IO-Link compatible	No
Max. output current	100 mA
Max. switching distance	8000 mm
Operating voltage (MAX)	30 V
Rated control supply voltage U_s at DC	10 V ... 30 V
Rated switching distance	8000 mm
Readiness delay	200 ms
Response time	25 ms
Scanning function	Light-/dark-on mode
Setting procedure	Manual adjustment
Switching frequency	1000 Hz
Type of alarm output	PNP
Type of electrical connection	Clamp
Type of input voltage	DC
Type of switching function	Programmable/configurable

ELECTRICAL DATA

Type of switching output	PNP
Voltage type	AC/DC
With communication interface, analog	No
With communication interface, AS-Interface	No
With communication interface, CANOpen	No
With communication interface, DeviceNet	No
With communication interface, Ethernet	No
With communication interface, INTERBUS	No
With communication interface, PROFIBUS	No
With communication interface, RS-232	No
With communication interface, RS-422	No
With communication interface, RS-485	No
With communication interface, SSD	No
With communication interface, SSI	No
With polarizing filter	Yes
With time function	No

OPTICAL DATA

Light beam form	Point
Light source	Polarized red light
Wavelength of the sensor	660 nm

DIMENSIONAL DRAWING

INSTALLATION



Mounting / Installation may only be carried out by a qualified electrician!

DISPOSAL



SAFETY WARNINGS

Before initial operation, please make sure to follow all safety instructions that may be provided in the product information!