




Product information M-XFP-SR/LC

Industrial Ethernet: System Accessories: Transceiver: 10 Gigabit Ethernet XFP and SFP+ Transceiver: M-XFP-SR/LC

<http://dev-catalog.beldensolutions.com/link/57078-24455-24544-24535-24530-40329/en/conf/uistate>

Name	M-XFP-SR/LC
	
	XFP Fiberoptic 10Gigabit-Ethernet Transceiver
Delivery informations	
Availability	available
Product description	
Description	XFP Fiberoptic 10Gigabit-Ethernet Transceiver
Order No.	943 917-001
Port type and quantity	1 x 10GBASE with LC Connector
Type	M-XFP-SR/LC
Network size - length of cable	
Multimode fiber (MM) 50/125 µm	0 – 66 m, 850 nm; 8.1 dB link budget, 3.0 dB/km, 400 MHz*km; 0-82 m, 850 nm; 8.1 dB link budget, 3.0 dB/km, 500 MHz*km (OM2); 0-300 m, 850 nm; 8.1 dB link budget, 3.0 dB/km, 2000 MHz*km (OM3)
Multimode fiber (MM) 62.5/125 µm	0 – 26 m, 850 nm; 8.1 dB link budget, 3.2 dB/km, 160 MHz*km; 0 – 33 m, 850 nm; 8.1 dB link budget, 3.2 dB/km, 200 MHz*km (OM1)
Service	
Diagnostics	optical input- and output power, transceiver temperature
Technical data	
Operating voltage	power supply via media module
Operating temperature	0 °C to +60 °C
Relative humidity (non-condensing)	5% - 95%
Power consumption	3 W
Approvals	
Basis Standard	FCC, RCM
Safety of information technology equipment	cUL 60950-1
Transportation	EN50121-4

For more information please contact:

Hirschmann Automation and Control GmbH

Stuttgarter Strasse 45-51

72654 Neckartenzlingen

Germany

Phone: +49 7127/14-1809

E-Mail: inet-sales@belden.com

The information published in the websites has been compiled as carefully as possible. It is subject to alteration without notice in technical as well as in price-related/commercial respect. The complete information and data were available on user documentation. Mandatory information can only be obtained by a concrete query.