



Product information

PTN-2-C37.94-E1 - PTN-2-C37.94-E1

Industrial Ethernet:DRAGON PTN:Modules :PTN-2-C37.94-E1	
http://dev-catalog.beldensolutions.com/link/57078-24455-502485-503713-503744/en/conf/uistate	
Name	PTN-2-C37.94-E1
	2 x C37.94 compliant SFP ports (LC, MM); 2 x E1 RJ45 ports; E1 (2.048 Mbps) compliant with ANSI T1.102, OFTEL OTR001 and ITU-T recommendations G.703 and G.823; 64 kbps cross connect per card; Up to 16 independent circuit emulated streams; CESoPSN and SAToP circuit emulation packet formats; Hitless switching (zero packet loss with 1+1 protection); Support for hair pinning mode (C37.94 to E1) without circuit emulation on a single card; Testing: Loopback, BERT; LAN operation
Delivery informations	
Availability	available
Product description	
Description	2 x C37.94 compliant SFP ports (LC, MM); 2 x E1 RJ45 ports; E1 (2.048 Mbps) compliant with ANSI T1.102, OFTEL OTR001 and ITU-T recommendations G.703 and G.823; 64 kbps cross connect per card; Up to 16 independent circuit emulated streams; CESoPSN and SAToP circuit emulation packet formats; Hitless switching (zero packet loss with 1+1 protection); Support for hair pinning mode (C37.94 to E1) without circuit emulation on a single card; Testing: Loopback, BERT; LAN operation
Type	PTN-2-C37.94-E1
Order No.	942 236-009

For more information please contact:

Hirschmann Automation and Control GmbH

Stuttgarter Strasse 45-51

72654 Neckartenzlingen

Germany

Phone: +49 7127/14-1809

E-Mail: inet-sales@belden.com

The information published in the websites has been compiled as carefully as possible. It is subject to alteration without notice in technical as well as in price-related/commercial respect. The complete information and data were available on user documentation. Mandatory information can only be obtained by a concrete query.