

**FY98C701**
**FILLING LEVEL SENSORS • OPTICAL**

Filling level and level sensors operate according to different measuring principles. The selection of the sensor depends on the medium to be detected and the ambient conditions. The material flow in a vibratory bowl can be excellently queried with inductive filling level sensors whose pendulum is moved by the material in the pot. The detection of liquid or solid media is, for instance, possible with capacitive filling level sensor technology. These work according to the principle of the condensator, the medium changes the dielectricity between two electrodes. The resulting change is converted into a digital output signal. A further alternative for the detection of filling levels of conductive media is provided by conductive filling level relays. The resistance between reference and measuring electrode is determined. If a set threshold is exceeded, a relay output switches.

**MECHANICAL DATA**

Ambient temperature	-10 °C ... 55 °C
Cable length	2 m
Degree of protection (IP)	IP50
Depth	26 mm
Height	28 mm
Housing design	Cuboid
Housing material	Polycarbonate
Medium temperature	-25 °C ... 50 °C
Number of wires	3
Width	16 mm

**ELECTRICAL DATA**

Max. output current	0.1 A
No-load current	25 mA
Number of pins	3
Physical measurement principle	Optic
Rated control supply voltage $U_s$ at DC	10 V ... 30 V
Reverse polarity protection	Yes
Short-circuit-proof	Yes
Type of electrical connection	Cable
Type of switching function	Normally closed contact/normally open contact
Type of switching output	PNP
Voltage drop	1 V
Voltage type for actuation	DC
With LED display	Yes

**DIMENSIONAL DRAWING****INSTALLATION**

Mounting / Installation may only be carried out by a qualified electrician!

**DISPOSAL****SAFETY WARNINGS**

Before initial operation, please make sure to follow all safety instructions that may be provided in the product information!