

VD58C269

ROTARY ENCODERS • ENCODERS

A rotary encoder is a device that converts a rotary motion into a digital output signal, which can be processed on a subsequent evaluation electronics. All of our encoders operate according to the principle of optical scanning. Inside the device there is a pulse disc on which is – depending on the encoder - a unique (absolute) or repetitive (incremental) line graduation, which is scanned by an optical system. The turning of the encoder shaft causes rotation of the pulse disc, which results in a corresponding sampling signal of the optical system. This is finally implemented by an integrated electronics in encoder-specific output signals (e.g. multi-turn, RS422 etc.). For professional installation in many applications, shaft couplings or resilient bases for mounting brackets or flanges are used. In addition, the encoder shaft can be equipped with measuring wheels or pinions in various designs and sizes. Typical applications include the angle measurement on bending machines, length measuring of belt systems or speed measurement on winding systems.

MECHANICAL DATA

Ambient temperature (MAX)	85 °C
Ambient temperature (MIN)	-25 °C
Degree of protection (IP)	IP54
Encoder size	58
Housing material	Aluminium
Max. rotation speed	6000 UpM
Moment of inertia	14.5 gcm ²
Sensor diameter	58 mm
Sensor length	52 mm
Shaft diameter (MAX)	12 mm
Shaft diameter (MIN)	12 mm
Shock resistance, acceleration	200 g
Shock resistance, pulse time	6 ms
Torque	0.03 Nm
Type of encoder shaft	Hollow shaft
Version	Incremental encoder
Vibration resistance, acceleration	10 g
Vibration resistance, frequency	2000 Hz
Weight	0.25 kg
With hollow shaft	Yes

ELECTRICAL DATA

Encoder signal outputs	A+B+0
Impulse rate per revolution (MAX)	5000
Impulse rate per revolution (MIN)	5000
Max. no. of pulses	5000
Max. output current	20 A

ELECTRICAL DATA

Max. output frequency	150000 Hz
No-load current	30 mA
Number of pins	12
Physical measurement principle	Optic
Programmable	No
Shaft length	52
Short-circuit-proof	Yes
Supply voltage (MAX)	30 V
Supply voltage (MIN)	4.75 V
Track A inverted	Yes
Type of electrical connection	Connector M23
Voltage type	DC

OTHER DATA

Air humidity	95 %
Relative air humidity	95 %
Single-turn encoder	Yes

DIMENSIONAL DRAWING

INSTALLATION



Mounting / Installation may only be carried out by a qualified electrician!

DISPOSAL



SAFETY WARNINGS

Before initial operation, please make sure to follow all safety instructions that may be provided in the product information!

Never use these devices in applications where the safety of a person depends on their functionality.