

VD58C415

ROTARY ENCODERS • ENCODERS

A rotary encoder is a device that converts a rotary motion into a digital output signal, which can be processed on a subsequent evaluation electronics. All of our encoders operate according to the principle of optical scanning. Inside the device there is a pulse disc on which is – depending on the encoder - a unique (absolute) or repetitive (incremental) line graduation, which is scanned by an optical system. The turning of the encoder shaft causes rotation of the pulse disc, which results in a corresponding sampling signal of the optical system. This is finally implemented by an integrated electronics in encoder-specific output signals (e.g. multi-turn, RS422 etc.). For professional installation in many applications, shaft couplings or resilient bases for mounting brackets or flanges are used. In addition, the encoder shaft can be equipped with measuring wheels or pinions in various designs and sizes. Typical applications include the angle measurement on bending machines, length measuring of belt systems or speed measurement on winding systems.

MECHANICAL DATA

Ambient temperature	-25 °C ... 85 °C
Cable length	1 m
Degree of protection (IP)	IP54
Encoder size	58
Housing material	Aluminium
Max. rotation speed	6000 UpM
Moment of inertia	14.5 gcm ²
Sensor diameter	58 mm
Sensor length	46 mm
Shaft diameter	12 mm ... 12 mm
Shock resistance, acceleration	200 g
Shock resistance, pulse time	6 ms
Torque	0.03 Nm
Type of encoder shaft	Hollow shaft
Version	Incremental encoder
Vibration resistance, acceleration	10 g
Weight	0.25 kg
With hollow shaft	Yes

ELECTRICAL DATA

Encoder signal outputs	A+B+0
Impulse rate per revolution	2500 ... 2500
Max. no. of pulses	2500
Max. output frequency	150000 Hz
No-load current	30 mA
Number of pins	12
Number of steps per revolution (MAX)	6000

ELECTRICAL DATA

Physical measurement principle	Optic
Programmable	No
Shaft length	22
Short-circuit-proof	Yes
Supply voltage	4.75 V ... 30 V
Track A inverted	Yes
Type of electrical connection	Cable radial
Voltage type	DC

OTHER DATA

Single-turn encoder	Yes
---------------------	-----

DIMENSIONAL DRAWING**INSTALLATION**

Mounting / Installation may only be carried out by a qualified electrician!

DISPOSAL**SAFETY WARNINGS**

Before initial operation, please make sure to follow all safety instructions that may be provided in the product information!