

CZ03C464**COUNTERS • TIME DELAY COUNTERS**

Elapsed-time counters are versatile. Various operating tasks can be solved by simple operating hour counters to the start- or stop-delay of switching signals up to the stopwatch in the millisecond range with adjustable switching threshold. In addition to the basic devices with largely fixed settings, multitalents can be set with parameters and functions via DIP-switches or membrane keyboard.

MECHANICAL DATA

Ambient temperature	-20 °C ... 70 °C
Degree of protection (IP)	IP65
Height	48 mm
Housing material	Plastic
Installation depth	38 mm
Length	38 mm
Mounting method	DIN rail
Storage temperature	70 °C
Storage temperature	-20 °C
Suitable for DIN rail (top hat rail) mounting	Yes
Width	48 mm

ELECTRICAL DATA

Adding	Yes
Display	Dial
Number of decades	7
Number of pins	2
Rated control supply voltage U_s at DC	10 V ... 80 V
Type of electrical connection	Screw connection
Type of signal input A	Two-wire
Voltage type	DC

DIMENSIONAL DRAWING**INSTALLATION****DISPOSAL**



Mounting / Installation may only be carried out by a qualified electrician!



SAFETY WARNINGS

Before initial operation, please make sure to follow all safety instructions that may be provided in the product information!