




Product information PSW 5-20

Industrial Ethernet: System Accessories: Power Supplies and Cables: Power Supplies: PSW 5-20

<http://dev-catalog.beldensolutions.com/link/57078-24455-24544-24545-503476-38463/en/conf/ui/state>

Name	PSW 5-20
	
	plug-in power supply
Delivery informations	
Availability	available
Product description	
Description	plug-in power supply
Type	PSW 5-20
Order No.	943 008-001
Electrical interfaces	
Input voltage	90 to 260 VAC; 50 to 60 Hz
Current consumption	60 mA
Power consumption	-
Output voltage	+5 V
Output current	max. 2.0 A
Ripple voltage	max. 100 mVpp
More Interfaces	
Voltage output	extra-low voltage plug, design M8 acc. IEC 947-5-2
Ambient conditions	
Operating temperature	0 °C to +40 °C
Storage/transport temperature	-40 °C to +70 °C
Relative humidity (non-condensing)	10% to 95%
Mechanical construction	
Weight	200 g
EMC interference immunity	
EN 61000-6-2 Immunity for industrial environments	EN 61000-6-2
EMC emitted immunity	
EN 55022	EN 55022 limit class B, EN 55024
Approvals	
Safety of information technology equipment	IEC 60950, IEC 60065
Scope of delivery and accessories	
Scope of delivery	device

For more information please contact:

Hirschmann Automation and Control GmbH

Stuttgarter Strasse 45-51

72654 Neckartenzlingen

Germany

Phone: +49 7127/14-1809

E-Mail: inet-sales@belden.com

The information published in the websites has been compiled as carefully as possible. It is subject to alteration without notice in technical as well as in price-related/commercial respect. The complete information and data were available on user documentation. Mandatory information can only be obtained by a concrete query.