




## Product information MB-2T

Industrial Ethernet:Modular Industrial Switches:Accessories:MB-2T

<http://dev-catalog.beldensolutions.com/link/57078-24455-49860-24489-40333/en/conf/ui/istate>

Name	MB-2T
	
	Expansion backplane with 2 slots for MS20/30-16 and MS4128 MICE switches
<b>Delivery informations</b>	
Availability	available
<b>Product description</b>	
Description	Expansion backplane with 2 slots for MS20/30-16 and MS4128 MICE switches
Port type and quantity	2 slots integrated on backplane (8 ports possible via media modules)
Type	MB-2T
Order No.	943 733-102
<b>Power requirements</b>	
Power consumption	0 W
<b>Ambient conditions</b>	
Operating temperature	0 °C bis +60 °C standart ( optional -40°C to +70°C)
Storage/transport temperature	-25 °C to +70 °C
Relative humidity (non-condensing)	10% to 95%
MTBF	1146.1 years; MIL-HDBK 217F: Gb 25 °C
<b>Mechanical construction</b>	
Dimensions (W x H x D)	79 mm x 134 mm x 22 mm
Mounting	DIN Rail 35 mm
Weight	150 g
Protection class	IP 20
<b>Mechanical stability</b>	
IEC 60068-2-27 shock	15 g, 11 ms duration, 18 shocks
IEC 60068-2-6 vibration	1 mm, 2 Hz - 13.2 Hz, 90 min.; 0.7g, 13.2 Hz - 100 Hz, 90 min.; 3.5 mm, 3 Hz - 9 Hz, 10 cycles, 1 octave/min.; 1g, 9 Hz - 150 Hz, 10 cycles, 1 octave/min.
<b>EMC interference immunity</b>	
EN 61000-4-2 electrostatic discharge (ESD)	6 kV contact discharge, 8 kV air discharge
EN 61000-4-3 electromagnetic field	10 V/m (80 - 1000 MHz)
EN 61000-4-4 fast transients (burst)	2 kV power line, 1 kV data line
EN 61000-4-5 surge voltage	Power line: 2 kV (line/earth), 1 kV (line/line), 1 kV data line
EN 61000-4-6 conducted immunity	3 V (10 kHz - 150 kHz), 10 V (150 kHz - 80 MHz)
<b>EMC emitted immunity</b>	
FCC CFR47 Part 15	FCC CFR47 Part 15 Class A
EN 55022	EN 55022 Class A
<b>Approvals</b>	
Safety of industrial control equipment	cUL 508
Shipbuilding	Germanischer Lloyd, ABS, BV, DNV, LR, KR, RINA
Railway norm	EN50121-4

For more information please contact:

**Hirschmann Automation and Control GmbH**

Stuttgarter Strasse 45-51

72654 Neckartenzlingen

Germany

Phone: +49 7127/14-1809

E-Mail: [inet-sales@belden.com](mailto:inet-sales@belden.com)

The information published in the websites has been compiled as carefully as possible. It is subject to alteration without notice in technical as well as in price-related/commercial respect. The complete information and data were available on user documentation. Mandatory information can only be obtained by a concrete query.