




Product information

Tofino Xenon - TofinoXe-0200M2S2SDDZ90003TAT03.2.

Industrial Ethernet:Industrial Firewall System:TOFINO XENON:Tofino Xenon	
http://dev-catalog.beldensolutions.com/link/57078-24455-49853-411807-411957/en/TofinoXe-0200M2S2SDDZ90003TAT03.2./uistate	
Name	Tofino Xenon
	
Delivery informations	
Availability	available
Product description	
Type	TofinoXe-0200M2S2SDDZ90003TAT03.2.
Order No.	TofinoXe-0200M2S2SDDZ90003TAT03.2.
Classification	
Belden brand	Hirschmann
More Interfaces	
Power supply/signaling contact	1 x plug-in terminal block, 6-pin
Digital Input	1 x plug-in terminal block, 2-pin
V.24 interface	1 x RJ11 socket
USB interface	1 x USB to connect the AutoConfiguration Adapter ACA21-USB
Network size - cascability	
Line - / star topology	any
Power requirements	
Operating voltage	12/24/48 V DC/24V AC (redundant)
Software	
Stateful inspection firewall	Stateful layer 2, 3 and 4 filtering with optional deep packet inspection for SCADA protocols (depending on purchased LSMs)
Management	Tofino Configurator software
Diagnostics	LEDs (power, mode, fault, save/load, reset , link status), signal contact, syslog, configuration verify. Captured by a syslog server or locally into nonvolatile memory for later download via network or USB storage device
Configuration	Network: Tofino Configurator uses secure communications to configure the Tofino Xenon security appliance Manual: Encrypted configuration files may be saved on a USB storage device and loaded into the Tofino Xenon security appliance via a secure USB
Ambient conditions	
Operating temperature	0 °C ... 60 °C
Storage/transport temperature	-40 °C ... 85 °C
Relative humidity (non-condensing)	10 % ... 95 %
Mechanical construction	
Dimensions (W x H x D)	60 mm x 145 mm x 125 mm
Mounting	DIN Rail
Weight	660 g
Protection class	IP20
Scope of delivery and accessories	
Scope of delivery	Device, terminal blocks, operating instructions, manual on CD
Accessories to order separately	Rail power supply RPS 30, RPS 80 EEC, RPS 120 EEC,Tofino Configurator software, ACA21-USB EEC, 19" installation frame, Tofino Firewall LSM, Tofino Modbus TCP Enforcer LSM, Tofino OPC Classic Enforcer LSM, Tofino NetConnect LSM, Tofino EtherNet/IP Enforcer LSM

For more information please contact:

Hirschmann Automation and Control GmbH



HIRSCHMANN

A **BELDEN** BRAND

Stuttgarter Strasse 45-51
72654 Neckartenzlingen
Germany
Phone: +49 7127/14-1809
E-Mail: inet-sales@belden.com

The information published in the websites has been compiled as carefully as possible. It is subject to alteration without notice in technical as well as in price-related/commercial respect. The complete information and data were available on user documentation. Mandatory information can only be obtained by a concrete query.