




Product information

Tofino Xenon - TofinoXe-0200T1T1SDDZ90003TAT03.2.

| Industrial Ethernet:Industrial Firewall System:TOFINO XENON:Tofino Xenon | |
|---|---|
| http://dev-catalog.beldensolutions.com/link/57078-24455-49853-411807-411957/en/TofinoXe-0200T1T1SDDZ90003TAT03.2./uistate | |
| Name | Tofino Xenon |
|  | |
| Delivery informations | |
| Availability | available |
| Product description | |
| Type | TofinoXe-0200T1T1SDDZ90003TAT03.2. |
| Order No. | TofinoXe-0200T1T1SDDZ90003TAT03.2. |
| Classification | |
| Belden brand | Hirschmann |
| More Interfaces | |
| Power supply/signaling contact | 1 x plug-in terminal block, 6-pin |
| Digital Input | 1 x plug-in terminal block, 2-pin |
| V.24 interface | 1 x RJ11 socket |
| USB interface | 1 x USB to connect the AutoConfiguration Adapter ACA21-USB |
| Network size - cascability | |
| Line - / star topology | any |
| Power requirements | |
| Operating voltage | 12/24/48 V DC/24V AC (redundant) |
| Software | |
| Stateful inspection firewall | Stateful layer 2, 3 and 4 filtering with optional deep packet inspection for SCADA protocols (depending on purchased LSMs) |
| Management | Tofino Configurator software |
| Diagnostics | LEDs (power, mode, fault, save/load, reset , link status), signal contact, syslog, configuration verify. Captured by a syslog server or locally into nonvolatile memory for later download via network or USB storage device |
| Configuration | Network: Tofino Configurator uses secure communications to configure the Tofino Xenon security appliance Manual: Encrypted configuration files may be saved on a USB storage device and loaded into the Tofino Xenon security appliance via a secure USB |
| Ambient conditions | |
| Operating temperature | 0 °C ... 60 °C |
| Storage/transport temperature | -40 °C ... 85 °C |
| Relative humidity (non-condensing) | 10 % ... 95 % |
| Mechanical construction | |
| Dimensions (W x H x D) | 60 mm x 145 mm x 125 mm |
| Mounting | DIN Rail |
| Weight | 660 g |
| Protection class | IP20 |
| Scope of delivery and accessories | |
| Scope of delivery | Device, terminal blocks, operating instructions, manual on CD |
| Accessories to order separately | Rail power supply RPS 30, RPS 80 EEC, RPS 120 EEC,Tofino Configurator software, ACA21-USB EEC, 19" installation frame, Tofino Firewall LSM, Tofino Modbus TCP Enforcer LSM, Tofino OPC Classic Enforcer LSM, Tofino NetConnect LSM, Tofino EtherNet/IP Enforcer LSM |

For more information please contact:

Hirschmann Automation and Control GmbH



HIRSCHMANN

A **BELDEN** BRAND

Stuttgarter Strasse 45-51
72654 Neckartenzlingen
Germany
Phone: +49 7127/14-1809
E-Mail: inet-sales@belden.com

The information published in the websites has been compiled as carefully as possible. It is subject to alteration without notice in technical as well as in price-related/commercial respect. The complete information and data were available on user documentation. Mandatory information can only be obtained by a concrete query.