



## Product information MACH1000, Full Gigabit Ethernet switch 16 ports - MAR1040-4C4C4C4C9999SM9HPHH09.0.

Industrial Ethernet:Ruggedized Switches:Fast/Gigabit Ethernet Control Cabinet Switches:Full Gigabit Ethernet Control Cabinet Switches:MACH1000, Full Gigabit Ethernet switch 16 ports	
<a href="http://dev-catalog.beldensolutions.com/link/57078-24455-49846-49997-82828-437642/en/MAR1040-4C4C4C4C9999SM9HPHH09.0/uistate">http://dev-catalog.beldensolutions.com/link/57078-24455-49846-49997-82828-437642/en/MAR1040-4C4C4C4C9999SM9HPHH09.0/uistate</a>	
Name	MACH1000, Full Gigabit Ethernet switch 16 ports
	
	Ethernet/Fast Ethernet/Gigabit Ethernet switch, managed, Industrial Switch 19" rack mount, fanless design
Delivery informations	
Availability	available
Product description	
Description	Ethernet/Fast Ethernet/Gigabit Ethernet switch, managed, Industrial Switch 19" rack mount, fanless design
Port type and quantity	16 x combo ports (10/100/1000BASE TX RJ45 plus related FE/GE-SFP slot)
Type	MAR1040-4C4C4C4C9999SM9HPHH09.0.
Order No.	942 004-001
More Interfaces	
Power supply/signaling contact	power supply 1: power supply, 3 pin plug-in terminal block, signal contact, 2 pin plug-in terminal block;
V.24 interface	1 x RJ11 socket
USB interface	1 x USB to connect the AutoConfiguration Adapter ACA21-USB
Network size - length of cable	
Twisted pair (TP)	0 m ... 100 m
Multimode fiber (MM) 50/125 µm	cf. Gigabit and Fast Ethernet SFP modules
Multimode fiber (MM) 62.5/125 µm	cf. Gigabit and Fast Ethernet SFP modules
Single mode fiber (SM) 9/125 µm	cf. Gigabit and Fast Ethernet SFP modules
Single mode fiber (LH) 9/125 µm (long haul transceiver)	cf. Gigabit and Fast Ethernet SFP modules
Network size - cascading	
Line - / star topology	any
Ring structure (HIPER-Ring) quantity switches	up to 10 ms (10 switches), up to 30 ms (50 switches), up to 40 ms (100 switches), up to 60 ms (200 switches)
Power requirements	
Operating voltage	power supply 1: 120/250 V DC; 110/230 V AC
Current consumption at 24 V DC	power supply 1: n/a;
Current consumption at 230 V AC	power supply 1: 110 mA (26 W) max., if all ports are equipped with SFP (100 W PoE option);
Power output in Btu (IT) h	90 max (350 PoE option)
Software	
Switching	Disable Learning (hub functionality); Independent VLAN Learning; Fast Aging; Static Unicast/Multicast Address Entries; QoS / Port Prioritization (802.1D/p); TOS/DSCP Prioritization; Egress Broadcast Limiter per Port; Flow Control (802.3X); VLAN (802.1Q); GARP VLAN Registration Protocol (GVRP); Double VLAN Tagging (QinQ); Voice VLAN; GARP Multicast Registration Protocol (GMRP); IGMP Snooping/Querier (v1/v2/v3); Jumbo Frames
Management	Dual Software Image Support; TFTP; LLDP (802.1AB); LLDP-MED; SSHv1; SSHv2; V.24; HTTP; HTTPS; Traps; SNMP v1/v2/v3; Telnet
Diagnostics	Management Address Conflict Detection; Address Relearn Detection; MAC Notification; Signal Contact; Device Status Indication; TCPDump; LEDs; Syslog; Port Monitoring with Auto-Disable; Link Flap Detection; Overload Detection; Duplex Mismatch Detection; Link Speed and Duplex Monitoring; RMON (1,2,3,9); Port Mirroring 1:1; Port Mirroring 8:1; Port Mirroring N:1; System Information; Self-Tests on Cold Start; Copper Cable Test; SFP Management; Configuration Check Dialog; Switch Dump
Configuration	AutoConfiguration Adapter ACA11; Automatic Configuration Undo (roll-back); Configuration Fingerprint; BOOTP/DHCP Client with Auto-Configuration; DHCP Server: per Port; DHCP Server: Pools per VLAN; DHCP Server: Option 43; AutoConfiguration Adapter ACA21/22 (USB); HiDiscovery; DHCP Relay with Option 82; Command Line Interface (CLI); CLI Scripting; Full-featured MIB Support; Web-based Management; Context-sensitive Help
Security	IP-based Port Security; MAC-based Port Security; Port-based Access Control with 802.1X; Guest/unauthenticated VLAN; RADIUS VLAN Assignment; Multi-Client Authentication per Port; MAC Authentication Bypass; ACL Hit Counter; Access to Management restricted by VLAN; HTTPS Certificate Management; Restricted Management Access; Appropriate Use Banner; SNMP Logging; Local User Management; Remote Authentication via RADIUS



## Industrial Ethernet:Ruggedized Switches:Fast/Gigabit Ethernet Control Cabinet Switches:Full Gigabit Ethernet Control Cabinet Switches:MACH1000, Full Gigabit Ethernet switch 16 ports

<http://dev-catalog.beldensolutions.com/link/57078-24455-49846-49997-82828-437642/en/MAR1040-4C4C4C9999SM9HPHH09.0./uistate>

<b>Redundancy functions</b>	Advanced Ring Configuration for MRP; HIPER-Ring (Manager); HIPER-Ring (Ring Switch); Link Aggregation with LACP; Media Redundancy Protocol (MRP) (IEC62439-2); Redundant Network Coupling; Sub Ring Manager; RSTP 802.1D-2004 (IEC62439-1); MSTP (802.1Q); RSTP Guards; RSTP over MRP; Fast HIPER-Ring
<b>Industrial Profiles</b>	EtherNet/IP Protocol; IEC61850 Protocol (MMS Server, Switch Model); PROFINET IO Protocol
<b>Time synchronisation</b>	Buffered Real Time Clock; SNTP Client; SNTP Server; PTPv2 Transparent Clock two-step; PTPv2 Boundary Clock
<b>Miscellaneous</b>	Manual Cable Crossing
<b>Ambient conditions</b>	
<b>Operating temperature</b>	0 °C ... 60 °C
<b>Storage/transport temperature</b>	-40 °C ... 85 °C
<b>Relative humidity (non-condensing)</b>	5 % ... 95 %
<b>MTBF</b>	13.6 years (MIL-HDBK-217F)
<b>Protective paint on PCB</b>	No
<b>Mechanical construction</b>	
<b>Dimensions (W x H x D)</b>	445 mm x 44 mm x 345 mm
<b>Mounting</b>	19" control cabinet
<b>Weight</b>	5600 g
<b>Protection class</b>	IP30
<b>Mechanical stability</b>	
<b>IEC 60068-2-27 shock</b>	15 g, 11 ms duration, 18 shocks
<b>IEC 60068-2-6 vibration</b>	1 mm, 2 Hz-13.2 Hz, 90 min.; 0.7g, 13.2 Hz-100 Hz, 90 min.; 3.5 mm, 3 Hz-9 Hz, 10 cycles, 1 octave/min.; 1 g, 9 Hz-150 Hz, 10 cycles, 1 octave/min.
<b>EMC interference immunity</b>	
<b>EN 61000-4-2 electrostatic discharge (ESD)</b>	8 kV contact discharge, 15 kV air discharge
<b>EN 61000-4-3 electromagnetic field</b>	35 V/m (80-2700 MHz); 1 kHz, 80% AM
<b>EN 61000-4-4 fast transients (burst)</b>	4 kV power line, 4 kV data line
<b>EN 61000-4-5 surge voltage</b>	power line: 2 kV (line/earth), 1 kV (line/line), 1 kV data line, IEEEE1613: power line 5 kV (line/earth)
<b>EN 61000-4-16 mains frequency voltage</b>	30 V, 50 Hz continuous; 300 V, 50 Hz 1 s
<b>EMC emitted immunity</b>	
<b>FCC CFR47 Part 15</b>	FCC 47 CFR Part 15 Class A
<b>EN 55022</b>	EN 55022 Class A
<b>Approvals</b>	
<b>Safety of industrial control equipment</b>	cUL 508
<b>Hazardous locations</b>	ISA 12.12.01 Class 1 Div. 2
<b>Shipbuilding</b>	DNV GL
<b>Substation</b>	IEC 61850-3, IEEE 1613
<b>Transportation</b>	EN 50121-4, EN50155, NEMA TS
<b>Scope of delivery and accessories</b>	
<b>Scope of delivery</b>	device, operating manual

For more information please contact:

**Hirschmann Automation and Control GmbH**

Stuttgarter Strasse 45-51

72654 Neckartenzlingen

Germany

Phone: +49 7127/14-1809

E-Mail: [inet-sales@belden.com](mailto:inet-sales@belden.com)

The information published in the websites has been compiled as carefully as possible. It is subject to alteration without notice in technical as well as in price-related/commercial respect. The complete information and data were available on user documentation. Mandatory information can only be obtained by a concrete query.