



Product information Configurable Gigabit Industrial Firewall System - EAGLE30-0402206TT999SCCZ9HSEOP03.0.

Industrial Ethernet:Industrial Firewall System:EAGLE20/30:with HiSec0S 3.0:Configurable Gigabit Industrial Firewall System	
http://dev-catalog.beldensolutions.com/link/57078-24455-49853-206245-438170-438168/en/EAGLE30-0402206TT999SCCZ9HSEOP03.0/ui/state	
Name	Configurable Gigabit Industrial Firewall System
	
	Industrial firewall and security router, DIN rail mounted, fanless design. Fast Ethernet, Gigabit Uplink type. 4 x 10/100 Mbit/s Ethernet Ports, 2 x 100/1000 Mbit/s Ethernet Ports, 2 x SFP slots, Twisted Pair / RJ45.
Delivery informations	
Availability	available
Product description	
Description	Industrial firewall and security router, DIN rail mounted, fanless design. Fast Ethernet, Gigabit Uplink type. 4 x 10/100 Mbit/s Ethernet Ports, 2 x 100/1000 Mbit/s Ethernet Ports, 2 x SFP slots, Twisted Pair / RJ45.
Port type and quantity	6 ports in total, Ports Fast Ethernet: 4 x 10/100BASE TX, RJ45 ; Gigabit Ethernet Ports: 2 ; Uplink Ports: 2 x SFP slot
More interfaces	
Power supply	2 x plug-in terminal block, 2-pin
Signaling contact	1 x plug-in terminal block, 2-pin
Digital Input	1 x plug-in terminal block, 2-pin
V.24 interface	1 x RJ11 socket
USB interface	1 x USB to connect the AutoConfiguration Adapter ACA22-USB
SD-card slot	1 x SD card slot to connect the auto configuration adapter ACA31
Network size - length of cable	
Twisted pair (TP)	0 m ... 100 m
Multimode fiber (MM) 50/125 µm	see SFP LWL-Modul M-SFP-SX/LC and M-SFP-LX/LC
Multimode fiber (MM) 62.5/125 µm	see SFP LWL-Modul M-SFP-SX/LC and M-SFP-LX/LC
Single mode fiber (SM) 9/125 µm	see SFP LWL-Modul M-SFP-LX/LC
Single mode fiber (LH) 9/125 µm (long haul transceiver)	see SFP LWL-Modul M-SFP-LH/LC and M-SFP-LH+/LC
Network size - cascading	
Line - / star topology	any
Power requirements	
Operating voltage	2 x 24/36/48 VDC (18-60 VDC)
Power consumption	14 W
Security	
Deep Packet Inspection	Enforcer "OPC Classic"
Encryption	Enhanced encryption (>56 Bit, up to 256Bit DES) Management access
Software	
Multipoint VPN	IPSec VPN
Ambient conditions	
Operating temperature	0 °C ... 60 °C
Storage/transport temperature	-40 °C ... 85 °C
Relative humidity (non-condensing)	10 % ... 95 %
Mechanical construction	
Dimensions (W x H x D)	90 mm x 164 mm x 120 mm
Mounting	DIN Rail
Weight	1200 g
Protection class	IP20
Mechanical stability	
IEC 60068-2-27 shock	15 g, 11 ms duration, 18 shocks
IEC 60068-2-6 vibration	1 mm, 2 Hz-13.2 Hz, 90 min.; 0.7 g, 13.2 Hz-100 Hz, 90 min.; 3.5 mm, 3 Hz-9 Hz, 10 cycles, 1 octave/min.; 1 g, 9 Hz-150 Hz, 10 cycles, 1 octave/min



Industrial Ethernet:Industrial Firewall System:EAGLE20/30:with HiSecOS 3.0:Configurable Gigabit Industrial Firewall System

<http://dev-catalog.beldensolutions.com/link/57078-24455-49853-206245-438170-438168/en/EAGLE30-0402206TT999SCCZ9HSEOP03.0./uistate>

EMC interference immunity

EN 61000-4-2 electrostatic discharge (ESD)	8 kV contact discharge, 15 kV air discharge
EN 61000-4-3 electromagnetic field	35 V/m (80-2700 MHz); 1 kHz, 80% AM
EN 61000-4-4 fast transients (burst)	4 kV power line, 4 kV data line
EN 61000-4-5 surge voltage	power line: 2 kV (line/earth), 1 kV (line/line), 1 kV data line, IEEE1613: power line 5 kV (line/earth)
EN 61000-4-6 conducted immunity	10 V (150 kHz-80 MHz)

EMC emitted immunity

FCC CFR47 Part 15	FCC 47 CFR Part 15 Class A
EN 55022	EN 55022 Class A

Approvals

Basis Standard	CE; C-Tick; EN 61131; EN 60950
----------------	--------------------------------

Scope of delivery and accessories

Scope of delivery	Device, terminal block, operating instructions, manual on CD
Accessories to order separately	Rail power supply RPS 30, RPS 80 EEC, RPS 120 EEC, terminal cable, network management Industrial HiVision, auto-configuration adapter ACA22-USB EEC or ACA31, 19" installation frame

For more information please contact:

Hirschmann Automation and Control GmbH

Stuttgarter Strasse 45-51

72654 Neckartenzlingen

Germany

Phone: +49 7127/14-1809

E-Mail: inet-sales@belden.com

The information published in the websites has been compiled as carefully as possible. It is subject to alteration without notice in technical as well as in price-related/commercial respect. The complete information and data were available on user documentation. Mandatory information can only be obtained by a concrete query.