

**OY300114**

**SAFETY SYSTEMS • LIGHT CURTAINS - HAND PROTECTION**

The multi-function light barriers are through-beam sensors where multiple beams are integrated. In case of interruption of only one beam, the switching output of the receiver changes its state. The devices are used where standard through-beam sensors with only one beam are not sufficient. There are devices with beam spacing of 20, 40, 60 or 120mm and different heights available. An integrated fuzzy logic controls the transmitting power automatically.

**MECHANICAL DATA**

Protected field height	1800 mm
Sensor length	40 mm

**ELECTRICAL DATA**

Cascadable	No
Clock control possible	No
Equipment protection class	Protection class 3
No-load current, transmitter	300 mA
Number of pins, receiver	5
Number of pins, transmitter	5
Override possible	No
Suitable for safety functions	Yes
Suppression possible	No
Switching voltage of OSSD at state "high"	24 V
Voltage type	DC
With LED display (7 segment)	Yes
With monitoring function of downstream devices	No
With muting function	No
With restart lock	No

**OPTICAL DATA**

Hand protection (< 30mm)	Yes
Protected field range	18 m

**OTHER DATA**

Explosion protection category for dust	None
Explosion protection category for gas	None
Scope of delivery of the one-way system	Transmitter and receiver
With beam coding	Yes

**DIMENSIONAL DRAWING****INSTALLATION**

Mounting / Installation may only be carried out by a qualified electrician!

**DISPOSAL****SAFETY WARNINGS**

Before initial operation, please make sure to follow all safety instructions that may be provided in the product information!