




## Part Number: RKWUE 19-242

M23 Power Single-Ended Cordset: Female, angled, 19-pin(18+PE), black body, 120 V AC/DC, 16x8 A + 2x10 A ; PUR black cable, 16x0.5 mm<sup>2</sup> + 3x1.0 mm<sup>2</sup>

### Product Description

M23 Power Single-Ended Cordset: Female, angled, 19-pin(18+PE), black body, 120 V AC/DC, 16x8 A + 2x10 A ; PUR black cable, 16x0.5 mm<sup>2</sup> + 3x1.0 mm<sup>2</sup>

### Technical Drawing



### Technical Specifications

#### Technical Data

|                           |                                                    |
|---------------------------|----------------------------------------------------|
| Product Family:           | Power Connector                                    |
| Product Sub Family:       | M23 Power                                          |
| Brand:                    | Lumberg Automation                                 |
| Connector Type:           | Cordset, single ended                              |
| Type of Contact / Gender: | female                                             |
| Connector Design:         | angled                                             |
| Number of Pins:           | 19(18+PE)                                          |
| Shielding:                | Unshielded                                         |
| Attachment Type:          | Grounded Coupling Nut                              |
| Rated Voltage:            | 125 V                                              |
| Rated Impulse Voltage:    | 1.5 kV                                             |
| Operating Voltage:        | 120 V AC/DC                                        |
| Rated Current:            | 16 x 8 A (pin-Ø 1 mm), 2 x 10 A (contact-Ø 1.5 mm) |
| Insulation Resistance:    | > 10 <sup>9</sup> Ohm                              |
| Mating Cycles:            | ≤ 100                                              |

|                                  |                                        |
|----------------------------------|----------------------------------------|
| Ambient Temperature (Operation): | -25°C to +80°C                         |
| Protection Degree / IP Rating:   | IP67                                   |
| Pollution Degree:                | 3 acc. to DIN EN 60664-1 (VDE 0110-1)  |
| Clearance / Creepage Distance:   | acc. to DIN EN 60664-1 (VDE 0110-1)    |
| Overvoltage Category:            | II acc. to DIN EN 60664-1 (VDE 0110-1) |

### Materials

|                                      |                     |
|--------------------------------------|---------------------|
| Contact Base Material:               | CuZn                |
| Contact Plating:                     | Cu/Au               |
| Contact Bearer Material:             | PBT                 |
| Contact Bearer Color:                | white               |
| Flammability Class (Contact Bearer): | UL 94 V0            |
| Molded Body Material:                | TPU                 |
| Molded Body Color:                   | black               |
| Flammability Class (Molded Body):    | UL 94-HB            |
| Attachment Material:                 | CuZn, nickel-plated |
| O-Ring Material:                     | NBR                 |

### Cable Data

|                                           |                                                                   |
|-------------------------------------------|-------------------------------------------------------------------|
| Cable Number:                             | 242                                                               |
| Conductor Size:                           | 16x0.5mm² + 3x1.0 mm²                                             |
| Number of Wires:                          | 19                                                                |
| Minimal Bending Radius (Fixed Inst):      | > 5 x D                                                           |
| Minimal Bending Radius (Flexible Inst):   | > 10 x D                                                          |
| Cycles (Bending):                         | > 2 M                                                             |
| Conductor material:                       | Cu                                                                |
| Cable Jacket Material:                    | PUR                                                               |
| Cable Jacket Color:                       | black                                                             |
| Cable Diameter D:                         | Ø 11.60 ±0.30 mm                                                  |
| Wire Insulation Material:                 | PP                                                                |
| Insulated Wire Diameter:                  | 16x Ø1.45 mm + 3x Ø1.95 mm                                        |
| Ambient Temperature (Fixed Installation): | -50°C to +80°C                                                    |
| Ambient Temperature (Flex Installation):  | -25°C to +80°C                                                    |
| Ambient Temperature (Drag Chain Inst):    | max. +60°C                                                        |
| UL Cable Type:                            | AWM: 21198 / 20549                                                |
| Flammability Class (Cable Jacket):        | IEC 60332-2, VDE 0482-265-2-2, EN 50265-2-2, FT2; flame-retardant |

### Safety & Environmental Compliance

|                 |     |
|-----------------|-----|
| RoHS Compliant: | yes |
|-----------------|-----|

### Resistances

|              |                                         |
|--------------|-----------------------------------------|
| Halogenfree: | IEC 60754-1, VDE 0482-267, EN 50267-2-1 |
|--------------|-----------------------------------------|

### Notes

|                                     |                                                                                                                       |
|-------------------------------------|-----------------------------------------------------------------------------------------------------------------------|
| Protection Degree / IP Rating Note: | * only if mounted and locked in combination with Hirschmann / Lumberg connector.                                      |
| Note Derating:                      | * Notice derating                                                                                                     |
| Note:                               | Do not connect / disconnect under load.                                                                               |
| Particularities:                    | When the connector is unlocked and in risk of pollution the connector has to be covered with a protective cap ≥ IP54. |

#### Variants

| Item # | Item Description  | Cable Length |
|--------|-------------------|--------------|
| 9623   | RKWUE 19-242/1 M  | 1 m          |
| 60715  | RKWUE 19-242/5 M  | 5 m          |
| 60711  | RKWUE 19-242/10 M | 10 m         |
| 60712  | RKWUE 19-242/15 M | 15 m         |
| 60713  | RKWUE 19-242/20 M | 20 m         |
| 61247  | RKWUE 19-242/25 M | 25 m         |
| 61252  | RKWUE 19-242/30 M | 30 m         |
| 61249  | RKWUE 19-242/35 M | 35 m         |

|           |                   |      |
|-----------|-------------------|------|
| 61246     | RKWUE 19-242/40 M | 40 m |
| 934637711 | RKWUE 19-242/45 M | 45 m |
| 89052     | RKWUE 19-242/50 M | 50 m |
| 934637713 | RKWUE 19-242/60 M | 60 m |

© 2019 Belden, Inc

All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described here in are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "ASIS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden believes this product to be in compliance with all applicable environmental programs as listed in the data sheet. The information provided is correct to the best of Belden's knowledge, information and belief at the date of its publication. This information is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. The Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.