




## Product information RPS90/48V LV

Industrial Ethernet: System Accessories: Power Supplies and Cables: Power Supplies: RPS90/48V LV

<http://dev-catalog.beldensolutions.com/link/57078-24455-24544-24545-503476-40992/en/conf/ui/state>

Name	RPS90/48V LV
	
	48 V DC rail power supply unit
<b>Delivery informations</b>	
Availability	available
<b>Product description</b>	
Description	48 V DC rail power supply unit
Type	RPS90/48V LV
Order No.	943 980-001
<b>More Interfaces</b>	
Voltage input	1 terminal block, 2-pin
Voltage output	1 terminal block, 4-pin
<b>Power requirements</b>	
Operating voltage	24 V DC
<b>Input data</b>	
Input voltage	N/A
<b>Current consumption</b>	
Current consumption	24 V DC (4,2 A), 48 V DC (2,1 A)
Activation current	N/A
<b>Output data</b>	
Output voltage	48 - 54 V DC (typ. 48 V); externally adjustable
<b>Output current</b>	
Output current	1.9 A static at 48 V nominal
<b>Service</b>	
Diagnostics	LED (green)
<b>Redundancy</b>	
Redundancy functions	redundant power supply
<b>Ambient conditions</b>	
Operating temperature	-25 °C to +60 °C
Storage/transport temperature	-40 °C to +85 °C
Relative humidity (non-condensing)	max. 95 % without condensation
MTBF	1 878 940 h (according to MIL-HDBK-217 Ausgabe F Notice 2)
<b>Mechanical construction</b>	
Dimensions (W x H x D)	60 mm x 137 mm x 115 mm
Mounting	DIN Rail
Weight	770 g
Protection class	IP 30
<b>EMC interference immunity</b>	
EN 50082-1	EN 61000-6-1
EN 50082-2	EN 61000-6-2 (including EN 55024), EN 61850-3, IEC 61000-3-2, EN 50121-4, 50121-3-2, GL (pending)
<b>EMC emitted immunity</b>	
EN 50081-1	61000-6-3
EN 50081-2	61000-6-4, EN 55011, EN 55022 Klasse A, GL (pending), Netzrückwirkungen gemäß EN 61000-3-2
<b>Approvals</b>	
Safety of industrial control equipment	cUL 508 (pending)
Safety of information technology equipment	cUL 60950-1 (pending)
Hazardous locations	ISA 12.12.01 Class 1 Div. 2 (pending)

Industrial Ethernet: System Accessories: Power Supplies and Cables: Power Supplies: RPS90/48V LV

<http://dev-catalog.beldensolutions.com/link/57078-24455-24544-24545-503476-40992/en/conf/ui/state>

<b>Shipbuilding</b>	Germanischer Lloyd, ABS
<b>Employment in vehicles</b>	E1
<b>Railway norm</b>	EN 50121-4, EN50155
<b>Substation</b>	IEC 61850-3, IEEE 1613
<b>Scope of delivery and accessories</b>	
<b>Scope of delivery</b>	Rail Power Supply, Description and operating manual, 1 x terminal block, 2-pin, 1 x terminal block, 4-pin

For more information please contact:

**Hirschmann Automation and Control GmbH**

Stuttgarter Strasse 45-51

72654 Neckartenzlingen

Germany

Phone: +49 7127/14-1809

E-Mail: [inet-sales@belden.com](mailto:inet-sales@belden.com)

The information published in the websites has been compiled as carefully as possible. It is subject to alteration without notice in technical as well as in price-related/commercial respect. The complete information and data were available on user documentation. Mandatory information can only be obtained by a concrete query.